

FOURWHEEL DRIVE DUMPER

CAPACITY:

Max. safe load: 6000 kg
 Heaped: 3150L
 Struck: 2215L
 Water: 1645L

ENGINE:

JCB444T 4 cylinder Turbo
 Displacement: 4.4 L
 Max. power: 74.5KW/100bhp @ 2200 rpm
 Max. torque: 425Nm @ 1300 rpm
 Emissions: Euro 2 compliant

TRANSMISSION:

Torque converter c/w 4 speed forward and reverse power shuttle transmission
 Permanent 4 wheel drive

DRIVE CHARACTERISTICS:

Forward / Reverse	1st	0-4.5 km/h (0-2.8 mph)
	2nd	0-7.0 km/h (0-4.4 mph)
	3rd	0-14 km/h (0-8.7 mph)
	4th	0-27 km/h (0-16.9 mph)
Steering angle:	+/- 36°	
Turning circle:	9.8m	
Grade-ability:	50%	
Tyres:	405/70 R20 (traction Profile)	
Steering:	Priority load sensing hydrostatic centre pivot	
Working brakes:	Multi-plate oil immersed discs mounted on both axles	
Park brake:	Hand operated, locking on dry disc acting on gearbox	

NOISE LEVELS:

LWA 103dB(A)
 LPA 85dB(A)

TANK CAPACITIES:

Fuel: 70L
 Hydraulic: 70L

SKIP:

Hydraulically operated skip tipping to 95°
 Skip swivels past 180° for easy placement when driving along trenches (185° maximum)
 Automatic safety lock to hold skip in a central position when travelling
 Heavy duty fully welded skip with 8mm thick steel base, reinforced upper side walls for greater strength
 Operated by a multi axis joystick for increased performance

ELECTRICAL:

Heavy duty 663 Battery: 12V, 135Ah
 Wiring harness in protective sleeving
 Reversing alarm

HYDRAULICS:


Hydraulic test points fitted as standard
 Easy access return oil filter on top of tank
 Easy access pressure filter

SEATING & CONTROLS:

Adjustable suspension seat accessible from both sides
 Clear access across dumper via galvanised steps
 Extra wide brake pedal
 Super bright warning lights on fully featured display instrument
 Steel constructed centre console for extra leg protection
 Operator level gear selection lever with integrated clutch button
 Column mounted directional control lever
 Heater vent at foot level
 Anti-slip floor
 Horn operable from joystick

SERVICE ACCESS:

Easy access for service maintenance
 Lockable hinged engine cover
 Battery mounted in lockable step compartment
 Lockable tool box compartment on step
 Separate fuel & hydraulic filler flaps



FEATURES

- Unrivalled operator accessibility and comfort
- Power swivel skip enabling discharge either side
- Excellent rough terrain performance from permanent 4-wheel drive
- Heavy duty construction; skip manufactured from 8 mm steel plate and reinforced around top
- Column operated forward and reverse directions with acceleration by foot pedal
- Simple and safe operation; drive direction on the steering column
- Heavy duty centre console for leg protection
- Simple instrument panel including fuel gauge, hourmeter, warning lights for-parking brake, oil temperature, oil pressure, engine temperature
- Folding ROPS as standard
- Easy access to engine compartment for service and maintenance
- Recovery bracket as standard
- 100 HP engine / 74.5 KW
- Excellent power to weight ratio
- Theft deterrent Cesar Data Tag System as standard
- Ample ground clearance
- Superior turning circle
- Skip swivels over 180° for easy placement when driving along trenches (185° maximum)
- Skip tips over 90°
- Reversing alarm standard
- Handbrake safety device - will not move until released
- Lockable toolbox and battery compartment, both fully galvanised
- Separate fuel and hydraulic filler compartments
- Adjustable steering column
- Adjustable suspension seat
- Flashing beacon

OPTIONAL EQUIPMENT

- Road Light Kit
- Spare Wheel
- Biodegradable Hydraulic Oil
- FOPS Roof
- Skip manufactured from ST52 or Hardox
- Cab
- Shovel, spade and brush holders



NC Engineering (Hamiltonsbawn) Ltd

2 Killyrudden Road, Hamiltonsbawn
 Richhill, Co Armagh
 Northern Ireland BT61 9SF

Tel: +44 (0) 28 3887 1970
 Fax: +44 (0) 28 3887 0362

Email: sales@nc-engineering.com
 Web: www.nc-engineering.com